

ID Platform FAP50 Swipe OCR with smart card reader



PHYSICAL CHARACTERISTICS

DIMENSIONS & WEIGHT 288 mm x 177 mm x 37 mm | 1070 grams

SCREEN 7" TFT LCD | 1280x800 HD | 400 cd/m² | 16.7M Colors | Touch/Panel Glass: 0.7mm Corning Glass

GFF Sensor Type | Capacitive 5 Points Multi Touch | Possibility to add an Extra Tempered Glass Protection

CAMERA 8MP Fixed Focus Front Camera (IMX219) | 13MP Auto Focus Rear Camera (0V13850) | Dual Flash Light

BATTERY

Battery life over 8 hours | 1 x 12600 mAh | Removable battery | Robust 2.5mm | Power Jack socket for 12V / 2.5A charger

EXTENSION ANDUSB type C for service port | USB type A host connector **COMMUNICATION PORTS**2 Micro SIM/USIM slots (ISO7816) | 1 Micro SD Slot

AUDIO Audio Jack: Headset with Microphone | Bluetooth Headset Compatible | Loudspeaker 1W

SENSORS Light Sensor | Magnetometer | G sensor | Gyroscope | Vibrator

PERFORMANCE CHARACTERISTICS

PROCESSOR Octa Core SDM450 @ 1.8 GHz

MEMORY 16 GB eMMC + 2 GB DDR3 | MicroSD TFLASH: Up to 256 GB

OPERATING SYSTEM Android 9

USER ENVIRONMENT

IP SEALINGIP54 (The protection class against dust and water can be increased by a protective case to IP65 or even IP67) **TEMPERATURES**Operating Temperature: -20°C to +60°C | Storage Temperature: -30°C to +60°C | Humidity: 5 to 95% non-condensing

DROP SPECIFICATION Multiple drops from 1.2m | Compliant MIL-STD-810G

WIRELESS COMMUNICATIONS

BLUETOOTH 4.0 - Low Energy

WLAN WiFi 802.11 a/b/g/n/ac - Direct - HotSpot

WWAN 2G supported frequency bands: GSM(850), EGSM(900), DCS(1800), PCS(1900)

3G supported frequency bands: WCDMA Band 1,2,5,8

4G supported frequencies bands: LTE-FDD Band 1, 3, 7, 20, 28 A&B

LTE-TDD Band 40

INTEGRATED GPS GPS | A-GPS | GLONASS | BeiDou (active antenna)

IDENTIFICATION MODULE

CONTACTLESS CARD NFC: NXP IC on board (PN80T:PN553 + P73N2M0) Compliant with ISO14443 A/B and ISO15693

READER With Secure Element - Read / Write mode - HEC - Card Emulation

SECURE ELEMENT P73N2MP (NFC IC) | SIM/USIM socket (SWP IF with NFC IC + ISO7816 IF with CPU)

OCR READER Compliant 9303 ICAO

Machine Readable Passports: 2 lines of 44 characters

Machine Readable Visas: 2 lines of 44 characters, 2 lines of 36 characters
 Travel documents: 2 lines of 36 characters, 3 lines of 30 characters

BIOMETRICS READER

FINGERPRINT Integrated Biometrics "FIVE-0" (4-4-2) | Capacitive - LES technology (Light Emitting Sensor)

SCANNER Supported Image Formats WSQ (FBI-approved) | FBI PIV / FAP50 / FIPS 201 certified

Active area: 81.28 mm x 50.80 mm | Resolution: 500 PPI

IRIS SCANNER 2.4MP Rear Camera (IMX132) | Dual IR LED (SFH4787S)

CONTACT CARD & SAM Fully interoperable to read all types of e-ID documents Compliant with ISO 7816 1/2/3 (T=0 & T=1) | Compliant with CAC - PIV - TWIC

High performance smartcard interface supports up to 420kbps | 1x SAM slot | 1x Smartcard slot

REGULATORY

CERTIFICATION EU: CE certification | Other Countries: on demand